



# ダスターピット・排水柵の接続口の確認事項

**CHECK!** ご確認ください!! 〈流出用〉

- ① 流出口は横抜き？それとも下抜き？
- ② トラップは必要？
- ③ 流出口に用意する接続管は、ソケット、配管パイプ、ニップルのどのタイプ？
- ④ 配管の径はいくつ？
- ⑤ 横抜きの場合に付ける管底の高さは？
- ⑥ 横抜きの場合の流出方向は？

## ダスターピット・排水柵流出口（トラップ付） ※接続以降の配管は当社外工事とする。

   標準

排水方向	項目	接続先種類																																																																											
		ソケット	フランジ	パイプ																																																																									
たて	名称	TYPE A-1	TYPE B-1	TYPE C-1																																																																									
	仕様	 <table border="1"> <tr><th colspan="4">呼び径</th></tr> <tr><th>A</th><th>B</th><th>L</th><th>D</th></tr> <tr><td>40</td><td>11/2</td><td>28</td><td>53</td></tr> <tr><td>50</td><td>2</td><td>34</td><td>66</td></tr> <tr><td>65</td><td>2 1/2</td><td>39</td><td>82</td></tr> </table>	呼び径				A	B	L	D	40	11/2	28	53	50	2	34	66	65	2 1/2	39	82	 <table border="1"> <tr><th colspan="5">呼び径</th></tr> <tr><th>A</th><th>B</th><th>L</th><th>D</th><th>E</th></tr> <tr><td>65</td><td>2 1/2</td><td>79</td><td>76.3</td><td>155</td></tr> <tr><td>80</td><td>3</td><td>82</td><td>89.1</td><td>180</td></tr> <tr><td>100</td><td>4</td><td>90</td><td>114.3</td><td>200</td></tr> </table>	呼び径					A	B	L	D	E	65	2 1/2	79	76.3	155	80	3	82	89.1	180	100	4	90	114.3	200	 <table border="1"> <tr><th colspan="4">呼び径</th></tr> <tr><th>A</th><th>B</th><th>L</th><th>D</th></tr> <tr><td>50</td><td>2</td><td>34</td><td>66</td></tr> <tr><td>65</td><td>2 1/2</td><td>39</td><td>82</td></tr> </table>	呼び径				A	B	L	D	50	2	34	66	65	2 1/2	39	82												
	呼び径																																																																												
	A	B	L	D																																																																									
40	11/2	28	53																																																																										
50	2	34	66																																																																										
65	2 1/2	39	82																																																																										
呼び径																																																																													
A	B	L	D	E																																																																									
65	2 1/2	79	76.3	155																																																																									
80	3	82	89.1	180																																																																									
100	4	90	114.3	200																																																																									
呼び径																																																																													
A	B	L	D																																																																										
50	2	34	66																																																																										
65	2 1/2	39	82																																																																										
よこ	名称	TYPE D-1	TYPE E-1	TYPE F-1																																																																									
	仕様	 <table border="1"> <tr><th colspan="4">呼び径</th></tr> <tr><th>A</th><th>B</th><th>L</th><th>D</th></tr> <tr><td>40</td><td>11/2</td><td>28</td><td>53</td></tr> <tr><td>50</td><td>2</td><td>34</td><td>66</td></tr> <tr><td>65</td><td>2 1/2</td><td>39</td><td>82</td></tr> </table>	呼び径				A	B	L	D	40	11/2	28	53	50	2	34	66	65	2 1/2	39	82	 <table border="1"> <tr><th colspan="5">呼び径</th></tr> <tr><th>A</th><th>B</th><th>L</th><th>D</th><th>E</th></tr> <tr><td>65</td><td>2 1/2</td><td>50</td><td>76.3</td><td>155</td></tr> <tr><td>80</td><td>3</td><td>80</td><td>89.1</td><td>180</td></tr> <tr><td>100</td><td>4</td><td>80</td><td>114.3</td><td>200</td></tr> </table>	呼び径					A	B	L	D	E	65	2 1/2	50	76.3	155	80	3	80	89.1	180	100	4	80	114.3	200	 <table border="1"> <tr><th colspan="4">呼び径(設備塩ビ管)</th></tr> <tr><th>A</th><th>外径/内径</th><th>L</th><th>D</th></tr> <tr><td>40</td><td>48/40.8</td><td>50</td><td>38</td></tr> <tr><td>50</td><td>60/51.8</td><td>50</td><td>49</td></tr> <tr><td>65</td><td>76/67.8</td><td>50</td><td>65</td></tr> <tr><td>75</td><td>89/78</td><td>50</td><td>75</td></tr> <tr><td>100</td><td>114/100.8</td><td>50</td><td>98</td></tr> </table>	呼び径(設備塩ビ管)				A	外径/内径	L	D	40	48/40.8	50	38	50	60/51.8	50	49	65	76/67.8	50	65	75	89/78	50	75	100	114/100.8	50	98
	呼び径																																																																												
	A	B	L	D																																																																									
40	11/2	28	53																																																																										
50	2	34	66																																																																										
65	2 1/2	39	82																																																																										
呼び径																																																																													
A	B	L	D	E																																																																									
65	2 1/2	50	76.3	155																																																																									
80	3	80	89.1	180																																																																									
100	4	80	114.3	200																																																																									
呼び径(設備塩ビ管)																																																																													
A	外径/内径	L	D																																																																										
40	48/40.8	50	38																																																																										
50	60/51.8	50	49																																																																										
65	76/67.8	50	65																																																																										
75	89/78	50	75																																																																										
100	114/100.8	50	98																																																																										

## 出入口ピット専用流出口（トラップ付） ※接続以降の配管は当社外工事とする。

項目	接続先種類																	
	塩ビトラップ たて抜き	塩ビトラップ よこ抜き																
名称	TYPE H-1	TYPE I-1																
仕様	 <table border="1"> <tr><th colspan="2">呼び径</th></tr> <tr><th>A</th><th>外径</th></tr> <tr><td>50</td><td>60</td></tr> <tr><td>65</td><td>76</td></tr> <tr><td>75</td><td>89</td></tr> </table>	呼び径		A	外径	50	60	65	76	75	89	 <table border="1"> <tr><th colspan="2">呼び径</th></tr> <tr><th>A</th><th>外径</th></tr> <tr><td>50</td><td>60</td></tr> </table>	呼び径		A	外径	50	60
呼び径																		
A	外径																	
50	60																	
65	76																	
75	89																	
呼び径																		
A	外径																	
50	60																	



このマークのついている製品は当社HPより図面データのダウンロードができます

## ダスターピット・排水桝流出口（トラップなし） ※接続以降の配管は当社外工事とする。

排水方向	項目	接続先種類																																																																										
		ソケット	フランジ	パイプ																																																																								
たて	名称	ソケット <b>TYPE A-2</b>	フランジ <b>TYPE B-2</b>	パイプ <b>TYPE C-2</b>																																																																								
	仕様	<p>※取付高さの確認を してください。</p> <p>排出用:SUS304 ソケット(内ネジ)</p> <p>(a) 塩ビ管接続の場合 (b) 鋼管接続の場合</p> <p>バルブソケット 硬質塩化ビニル管</p> <p>ねじ接続 鋼管</p> <table border="1"> <tr><th colspan="4">呼び径</th></tr> <tr><th>A</th><th>B</th><th>L</th><th>D</th></tr> <tr><td>40</td><td>11/2</td><td>28</td><td>53</td></tr> <tr><td>50</td><td>2</td><td>34</td><td>66</td></tr> <tr><td>65</td><td>2 1/2</td><td>39</td><td>82</td></tr> </table>	呼び径				A	B	L	D	40	11/2	28	53	50	2	34	66	65	2 1/2	39	82	<p>※取付高さの確認を してください。</p> <p>排出用:フランジ(SUS JIS5K)</p> <p>フランジ接続 鋼管</p> <table border="1"> <tr><th colspan="5">呼び径</th></tr> <tr><th>A</th><th>B</th><th>L</th><th>D</th><th>E</th></tr> <tr><td>65</td><td>2 1/2</td><td>50</td><td>76.3</td><td>155</td></tr> <tr><td>80</td><td>3</td><td>80</td><td>89.1</td><td>180</td></tr> <tr><td>100</td><td>4</td><td>80</td><td>114.3</td><td>200</td></tr> </table>	呼び径					A	B	L	D	E	65	2 1/2	50	76.3	155	80	3	80	89.1	180	100	4	80	114.3	200	<p>※取付高さの確認を してください。</p> <p>排出用:SUS304 配管パイプ</p> <p>接続部コーキング (当社外工事) 硬質塩化ビニル管</p> <table border="1"> <tr><th colspan="4">呼び径(設備塩ビ管)</th></tr> <tr><th>A</th><th>外径/内径</th><th>L</th><th>D</th></tr> <tr><td>40</td><td>48/40.8</td><td>50</td><td>38</td></tr> <tr><td>50</td><td>60/51.8</td><td>50</td><td>49</td></tr> <tr><td>65</td><td>76/67.8</td><td>50</td><td>65</td></tr> <tr><td>75</td><td>89/78</td><td>50</td><td>75</td></tr> <tr><td>100</td><td>114/100.8</td><td>50</td><td>98</td></tr> </table>	呼び径(設備塩ビ管)				A	外径/内径	L	D	40	48/40.8	50	38	50	60/51.8	50	49	65	76/67.8	50	65	75	89/78	50	75	100	114/100.8	50
呼び径																																																																												
A	B	L	D																																																																									
40	11/2	28	53																																																																									
50	2	34	66																																																																									
65	2 1/2	39	82																																																																									
呼び径																																																																												
A	B	L	D	E																																																																								
65	2 1/2	50	76.3	155																																																																								
80	3	80	89.1	180																																																																								
100	4	80	114.3	200																																																																								
呼び径(設備塩ビ管)																																																																												
A	外径/内径	L	D																																																																									
40	48/40.8	50	38																																																																									
50	60/51.8	50	49																																																																									
65	76/67.8	50	65																																																																									
75	89/78	50	75																																																																									
100	114/100.8	50	98																																																																									
よこ	名称	ソケット <b>TYPE D-2</b>	フランジ <b>TYPE E-2</b>	パイプ <b>TYPE F-2</b>																																																																								
	仕様	<p>※取付高さの確認を してください。</p> <p>排出用:SUS304 ソケット (内ネジ)</p> <p>(a) 塩ビ管接続の場合 (b) 鋼管接続の場合</p> <p>バルブソケット 硬質塩化ビニル管</p> <p>ねじ接続 鋼管</p> <table border="1"> <tr><th colspan="4">呼び径</th></tr> <tr><th>A</th><th>B</th><th>L</th><th>D</th></tr> <tr><td>40</td><td>11/2</td><td>28</td><td>53</td></tr> <tr><td>50</td><td>2</td><td>34</td><td>66</td></tr> <tr><td>65</td><td>2 1/2</td><td>39</td><td>82</td></tr> </table>	呼び径				A	B	L	D	40	11/2	28	53	50	2	34	66	65	2 1/2	39	82	<p>※取付高さの確認を してください。</p> <p>排出用:フランジ(SUS JIS5K)</p> <p>鋼管 フランジ接続</p> <table border="1"> <tr><th colspan="5">呼び径</th></tr> <tr><th>A</th><th>B</th><th>L</th><th>D</th><th>E</th></tr> <tr><td>65</td><td>2 1/2</td><td>50</td><td>76.3</td><td>155</td></tr> <tr><td>80</td><td>3</td><td>80</td><td>89.1</td><td>180</td></tr> <tr><td>100</td><td>4</td><td>80</td><td>114.3</td><td>200</td></tr> </table>	呼び径					A	B	L	D	E	65	2 1/2	50	76.3	155	80	3	80	89.1	180	100	4	80	114.3	200	<p>※取付高さの確認を してください。</p> <p>排出用:SUS304 配管パイプ</p> <p>硬質塩化ビニル管 接続部コーキング (当社外工事)</p> <table border="1"> <tr><th colspan="4">呼び径(設備塩ビ管)</th></tr> <tr><th>A</th><th>外径/内径</th><th>L</th><th>D</th></tr> <tr><td>40</td><td>48/40.8</td><td>50</td><td>38</td></tr> <tr><td>50</td><td>60/51.8</td><td>50</td><td>49</td></tr> <tr><td>65</td><td>76/67.8</td><td>50</td><td>65</td></tr> <tr><td>75</td><td>89/78</td><td>50</td><td>75</td></tr> <tr><td>100</td><td>114/100.8</td><td>50</td><td>98</td></tr> </table>	呼び径(設備塩ビ管)				A	外径/内径	L	D	40	48/40.8	50	38	50	60/51.8	50	49	65	76/67.8	50	65	75	89/78	50	75	100	114/100.8	50
呼び径																																																																												
A	B	L	D																																																																									
40	11/2	28	53																																																																									
50	2	34	66																																																																									
65	2 1/2	39	82																																																																									
呼び径																																																																												
A	B	L	D	E																																																																								
65	2 1/2	50	76.3	155																																																																								
80	3	80	89.1	180																																																																								
100	4	80	114.3	200																																																																								
呼び径(設備塩ビ管)																																																																												
A	外径/内径	L	D																																																																									
40	48/40.8	50	38																																																																									
50	60/51.8	50	49																																																																									
65	76/67.8	50	65																																																																									
75	89/78	50	75																																																																									
100	114/100.8	50	98																																																																									

### CHECK! ご確認ください!! 〈流入用〉

- 排水ピットに流入口が接続される場合、接続位置の形状は直角? それとも 45°?
- 流入口に用意する接続管は、ソケット、配管パイプ、ニップルのどのタイプ?
- 配管の径はいくつ?
- ピット側に付ける管底の高さは?
- 流入側の配管は塩ビ管? それとも鋼管?

## ダスターピット流入用接続口バリエーション ※接続以降の配管は当社外工事とする。

項目	流入先 接続種類	流入口接続角度
仕様	<p>シーリング(当社外工事)</p> <p>開口</p> <p>25以上</p> <p>流入管</p>	<p>90°</p> <p>流入口は90度で接続</p>